


## Microphone Bridging Transformer



DUAL FARADAY SHIELDS FOR HIGH ISOLATION

- Provides additional, isolated balanced output as mic 'splitter'
- Solves 'transformerless' preamp problems when used as retrofit
- High common-mode rejection: 130 dB at 60 Hz
- Excellent frequency response and time domain performance
- Low insertion loss: 0.8 dB



This transformer is designed to be driven from a 150 Ω microphone source and loaded by the typical 1 kΩ input impedance of microphone preamplifiers. It can be used with balanced or unbalanced sources and/or loads since both primary and secondary are fully balanced. A 30 dB magnetic shield package is standard.





#30 AWG (7x38) UL STYLE 1061 COLOR CODED WIRE LEADS, 8" MINIMUM LENGTH



USE ONLY #4 TYPE B SELF TAPPING SCREWS IN HOLES "M". ALLOW NO MORE THAN 0.15" PENETRATION INTO TRANSFORMER HOUSING.








**JT-MB-C SPECIFICATIONS** (all levels are input unless noted)

PARAMETER	CONDITIONS	MINIMUM	TYPICAL	MAXIMUM
Input impedance, Zi	1 kHz, -20 dBu, test circuit 1	1.00 kΩ	1.06 kΩ	1.15 kΩ
Voltage gain	1 kHz, -20 dBu, test circuit 1	-0.90 dB	-0.82 dB	-0.70 dB
Magnitude response, ref 1 kHz	20 Hz, -20 dBu, test circuit 1	-0.50 dB	-0.14 dB	±0.0 dB
	20 kHz, -20 dBu, test circuit 1	-0.25 dB	-0.13 dB	+0.1 dB
Deviation from linear phase (DLP)	20 Hz to 20 kHz, -20 dBu, test circuit 1		+3.3/-0°	±5.0°
Distortion (THD)	1 kHz, -20 dBu, test circuit 1		0.001%	
	20 Hz, -20 dBu, test circuit 1		0.05%	0.15%
Maximum 20 Hz input level	1% THD, test circuit 1	0 dBu	+2.0 dBu	
Common-mode rejection ratio (CMRR) 150 Ω balanced source	60 Hz, test circuit 2		130 dB	
	3 kHz, test circuit 2	80 dB	95 dB	
Common-mode rejection ratio (CMRR) 150 Ω unbalanced source	60 Hz, test circuit 3		115 dB	
	3 kHz, test circuit 3		80 dB	
Output impedance, Zo	1 kHz, test circuit 1		245 Ω	
DC resistances	primary (RED to BRN)		48 Ω	
	secondary (YEL to ORG)		50 Ω	
Capacitances @ 1 kHz	primary to shield and case		54 pF	
	secondary to shield and case		67 pF	
Turns ratio		1:0.999	1:1.000	1:1.001
Temperature range	operation or storage	0° C		70° C
Breakdown voltage (see IMPORTANT NOTE below)	primary or secondary to shield and case, 60 Hz, 1 minute test duration	250 V RMS		

**IMPORTANT NOTE:** This device is NOT intended for use in life support systems or any application where its failure could cause injury or death. The breakdown voltage specification is intended to insure integrity of internal insulation systems; continuous operation at these voltages is NOT recommended. Consult our applications engineering department if you have special requirements.



All minimum and maximum specifications are guaranteed. Unless noted otherwise, all specifications apply at 25°C. Specifications subject to change without notice. All information herein is believed to be accurate and reliable, however no responsibility is assumed for its use nor for any infringements of patents which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Jensen Transformers, Inc.